How to Order Cantilever Shelving

- \bigcirc All cantilever shelving *requires* a left and a right upright.
 - Uprights include clips, welded every twelve inches, that allow cantilever shelves to lift and lock into place —no tools required.
- 0 Common uprights are used to build shelving runs longer than five feet and to connect sections with different shelf lengths.
- All freestanding cantilever units **require** a pair of horizontal braces for each section of the shelving unit.

Braces and shelves in a given section must have identical lengths.

Calculating Cantilever Shelving Length:

The required uprights, left and right, contribute an additional 2¾" to the total length of a shelving run. Therefore, each shelving unit — with or without common uprights — is 2¾" longer than the sum of each shelving section.

The unit in this photograph includes:

(1) Left Upright Model #2561

Select shelves and *required* braces:

- (1) Solid Brute 18" x 42" *Model #2542*
- (1) T-Bar 18" x 42" Model #2522
- (1) H.D. Bar 18" x 42" *Model #2502*
- (1) Set of Horizontal Braces Model #2582
- (1) Common Upright Model #2565

Select shelves and *required* braces:

- (1) Solid Brute 18" x 42" *Model #2542*
- (1) T-Bar 18" x 42" Model #2522
- (1) H.D. Bar 18" x 42" *Model #2502*
- (1) Set of Horizontal Braces Model #2582
- (1) Right Upright Model #2563



Shelving Section

2561